

Product information | DATA SHEET

OUTDOOR PROTECTIVE VARNISH

400 ml, 11.21 OZ, 318 -323 g

GENERAL DESCRIPTION

Outdoor Protective Varnish is a water-based indoor and outdoor varnish spray. Available in matte, satin and glossy finishes, it provides a uniform result with excellent hardness, flexibility and scratch resistance, as well as protection against UV rays.

FEATURES

- Fast drying.
- Good adhesion on porous materials and different paints.
- Excellent flexibility and hardness.
- Easy application and recoating.
- Glossy, satin and matte finishes.
- Low odor.
- UV protection.

INSTRUCTIONS FOR USE

- Shake the aerosol very well before use, approximately one minute after hearing the noise of the mixing ball.
- Apply on clean and dry surfaces.
On wood, prepare the wood properly before application. It can be applied directly to new wood after preparation. Sand imperfections or roughness if necessary. On painted or varnished wood, remove chipped and not peeling paints and varnishes by stripping, scraping or sanding. On plastics first apply a suitable primer according to the type of plastic. Do not apply directly to metal.
Do a preliminary test on other types of surfaces.
- Can be applied to solvent- and water-based acrylic paints, after drying.
Can be applied to acrylic chalky products. Compatible with MTN PRO products: RAL Colors, Metallic Paint, Vinyl Coating.
For other compatibilities please contact our Technical Dept.
- Apply in thin coats for best results; three thin coats are always better than one thick coat. Recoatable after 30-60 minutes with the same varnish. It is recommended to apply 2 or 3 coats depending on the porosity of the surface.
- Do not varnish in direct sunlight or on dew.
- Tools or product stains can be cleaned with soap and water.
- Do not apply to connected equipment and use in well-ventilated areas.
- Request safety data sheets.

PHYSICAL FEATURES

Binder type:	Polyurethane
Color:	Clear
Gloss:	Glossy >70 (60°)
	Satin 10-20 (60°)
	Matte <10 (60°)
Touch-dry (ASTM D-1640 ISO 1517):	30 -60'
VOCs:	500 g/L
Dry coat thickness:	7-8 micras
Recommended coat thickness:	2-3 coats*
Resistance to temperature:	90°C
Theoretical coverage:	2.5 m ² per 400 ml spray can
Recoat time:	20 minutes
Product life cycle:	5 years
Application conditions:	Room temp. 8°C
	Surface temp. 5°C
	Max. humidity 85% RHP
	Maximum room temp. 35°C

* Depending on the porosity of the surface.

051222

APPLICATIONS

In addition to its excellent adhesion and high mechanical resistance, it is suitable for protecting wood outdoors, such as doors, furniture, skirting boards, etc.

Depending on the porosity of the material to be varnished, two or three coats may be required.

IMAGE



DIFFUSER LABEL



MTN PRO Outdoor Glossy Protective Varnish
EX014PW0900E

MTN PRO Outdoor Satin Protective Varnish
EX014PW0904E

MTN PRO Outdoor Matte Protective Varnish
EX014PW0907E

PACKAGING

Rated capacity: 400 ml
Heat resistance of container: < 50°C
Propellant: DME

Box (6 pcs)
205 X 140 X 200 mm

