

Product information | TECHNICAL DATA SHEET

SPECTRAL. Semi-trasparent matte colors for creating special effects, shadows and three-dimensional effects. 400 ml, 10.6 Oz, 300 g.

GENERAL DESCRIPTION

Very low opacity, translucent, solvent-based acrylic paint formulated to create shadows and three-dimensional effects in the fields of graffiti, mural painting, decoration and fine arts.

FEATURES

- Fast drying.
- Good adherence.
- No vellowing.
- Does not contain lead nor other heavy metals.
- Easy to apply and repaint.
- Matte finish.
- It may also be considered a tinted varnish.
- More opacity can be obtained by applying in layers.

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- For best results apply in thin layers.
- Turn the aerosol upside down to clean out the valve after use. If te nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

Binder type:	Thermoplastic Acrylic
Color:	See Chart
Shine:	>10% Matte finish
Dry to the touch (ASTM D-1640 ISO 1517):	5'
Completely dry (ASTM D-1640 ISO 1517):	10 min
Thickness of dry layer	15 micras/capa
Thickness of dry layer (pintado contiuno):	2,5 m ²
Thinner:	Acetate
Repintado:	After de 5'
Product life:	>5 years
Heat resistance of paint:	160°C
Condition for application:	Tº Ambiente Mínima: 8°C
	Tº Superfície: 5-50°C
	Humedad Máx 85% R.H.P

COLORS



Montana Colors, S.L. P.I. Clot del Tufau - 08295 Sant Vicenç de Castellet BARCELONA

T.: +34 938 332 787 - montana@montanacolors.com - www.montanacolors.com

APPLICATIONS

As a result of the product's characteristics we recommend its use in the fields of:

- Fine arts - Graffiti - Sign painting - Scenography - Decoration -Crafts

The product may be applied to various surfaces. When applied to glass and some plastics, adhesion may be less effective.

IMAGE



LABEL **CAP SYSTEM**





PACKAGING

220920

Nominal capacity 400 ml. Heat resistanve of packaging: <50°C Propellant: DME

Box (6 units) 205 X 140 X 200 mm.











